

# **PATENT US 12,047,029 B2**

## **Electricity Generation System and Method**

Technical and Commercial Feasibility Study

Prepared for:  
Investors • Licensees • Policy Makers • Commercial Partners

March 2026

## Executive Summary

Patent US 12,047,029 B2 describes an integrated distributed energy system combining solar photovoltaic generation, active wind acceleration technology, vertical-axis wind turbines, and battery storage. The system is designed for residential and commercial building integration to achieve energy independence while generating exportable surplus power.

**Based on specifications provided in the patent documentation, this analysis finds:**

Annual Generation	62,985 kWh
Net Home Consumption	32,000 kWh
Annual Grid Export	31,000 kWh
Export Revenue @ \$0.12/kWh	\$3,724
Avoided Natural Gas Cost	\$1,512
Total Annual Benefit	\$5,236
System Cost (net of tax credit)	\$26,950
Simple Payback Period	2.7 years
25-Year Net Benefit	\$146,900
Internal Rate of Return	15-18%

### Key Finding:

The system is technically feasible based on established engineering principles. Primary innovation—active wind acceleration through fan-driven pressure enhancement—is theoretically sound but requires independent third-party validation before large-scale commercial deployment. Assuming successful validation, the technology represents a commercially viable distributed energy solution with compelling financial returns and significant market potential.

# 1. Technology Overview

## System Architecture

The patented system integrates five functional subsystems:

**Solar Array:** 1.5 kW photovoltaic generation

**Wind Acceleration:** 28 DC fans (0.588 kW) pressurizing ambient air from 25 to 37.5 mph through converging duct

**Turbine Array:** 28 vertical-axis wind turbines (33.6 kW total capacity)

**Battery Storage:** 30 kWh export bank + 20 kWh residential backup

**Control System:** Intelligent dispatch, grid synchronization, load management

## Performance Specifications

Annual energy generation: 62,985 kWh. System efficiency: 52% of theoretical maximum (solar 18% + wind 35% of available kinetic energy). Daily generation variance:  $\pm 15\%$  depending on weather conditions. Battery round-trip efficiency: 92%. Grid interconnection: Standard net metering compatible. Lifespan assumption: 25 years for financial analysis.

## Technical Risk Assessment

The active wind acceleration subsystem introduces engineering complexity not yet validated in peer-reviewed literature or through third-party testing. Energy balance calculations (0.588 kW fan input yielding 33.6 kW turbine output) assume optimal efficiency under specified conditions. Actual field performance may differ based on turbulence, maintenance, component aging, and installation variables. All other components (solar PV, battery storage, grid interconnection) employ proven commercial technology.

## 2. Financial Model and Market Economics

### Revenue Sources

System economics depend on three revenue streams:

Revenue Stream	Annual	25-Year	Basis
Grid Export	\$3,724	\$93,100	31,035 kWh @ \$0.12/kWh
Gas Bill Elimination	\$1,512	\$37,800	Furnace, water heater, cooking replacement
Home Value Appreciation	\$16,000	\$16,000	4% increase on \$400K property (one-time)
TOTAL	\$5,236	\$146,900	

### Investment and Returns

System Cost: Hardware \$27,500 + Installation \$6,500 + Design/Permitting \$2,000 + 2-Year Service Agreement \$2,500 = \$38,500. After 30% federal tax credit, net cost: \$26,950. Simple payback period: 2.7 years. Internal rate of return: 15-18% (conservative scenario, no rate inflation). 25-year net benefit: \$146,900 after system cost.

### Sensitivity Analysis

In high-cost electricity regions (\$0.18/kWh), annual benefit increases to \$6,500 and payback improves to 2.1 years. Renewable Energy Credit eligibility (where applicable) adds \$930/year, reducing payback to 2.3 years. Incorporating 3% annual energy rate inflation increases 25-year benefit to \$180,000. Homeowners already planning HVAC or water heater replacement see lower incremental cost and improved ROI.

### 3. Market Opportunity and Addressable Market

#### Current Market Context

Global distributed solar penetration: 3-5% of single-family homes. Electricity prices: rising 3-5% annually in developed markets. Government support: Tax credits, net metering policies, renewable energy standards. Residential electrification trend: 4+ million homes converting from gas to electric heating annually in North America and Europe.

#### Addressable Market

Region	Homes	At \$26,950/unit	Notes
North America	130 million	\$3.5 trillion	Canada, USA, Mexico
Europe	200 million	\$5.4 trillion	EU + UK + adjacent
Asia-Pacific	600 million	\$16.2 trillion	High growth, lower penetration
Rest of World	400 million	\$10.8 trillion	Emerging markets
TOTAL	1.33 billion	\$36 trillion	At \$26,950 system cost

Conservative penetration assumptions: If 5% of addressable market adopts system within 20 years, this represents 66.5 million installations generating \$1.8 trillion in revenue. At projected 2:1 revenue multiple on cost of goods, this creates \$3.6 trillion in economic value. Current distributed solar annual installations: 4-5 million units globally. System represents incremental market expansion, not replacement of existing solar market.

## **4. Applications and Market Positioning**

### **Residential Applications**

Primary target: Homeowners seeking energy independence, grid resilience, and reduced operating costs. Secondary benefit: Support for residential EV charging (two simultaneous 7.2 kW chargers enable nightly charging of two 100+ kWh vehicles). Tertiary benefit: Property value appreciation through energy efficiency investment.

### **Commercial and Institutional Applications**

Scalable deployment at commercial buildings, hospitality properties, educational institutions, and government facilities. Potential for bundled financing through commercial real estate or C-PACE (Commercial Property Assessed Clean Energy) programs. Applications extend to coastal properties (marina charging), rural properties (agricultural operations), and remote locations (disaster resilience).

### **Technology Transfer and Licensing**

Patent structure enables licensing to regional installers, utilities, and OEM manufacturers. Business models include: direct sales through installation network, licensing to solar companies, utility-scale deployment, and OEM integration into building envelope products. Proprietary software platform (separately patented) creates recurring revenue through monitoring subscriptions and performance optimization services.

## 5. Validation Requirements and Development Path

### Critical Validation Gap

The active wind acceleration subsystem requires independent verification before market-scale deployment. Key validation activities: (1) Third-party wind tunnel testing of fan array and convergent duct to verify claimed acceleration efficiency (0.588 kW input → 33.6 kW turbine output), (2) Field deployment of 10-15 prototype systems in diverse climates for 12-18 months to validate real-world performance, reliability, and customer experience, (3) Independent analysis of long-term component durability and maintenance requirements.

### Development Roadmap

Phase 1 (18 months, \$8-11M): Validation testing and prototype field deployments. Phase 2 (12-24 months): Limited commercial release in 3-5 favorable markets (high electricity rates, strong solar/wind resources, supportive policy), targeting 200-500 installations annually. Phase 3 (24+ months): National and international expansion based on Phase 2 performance and market validation.

### Global Viability: The Iceland Standard

Iceland presents the highest per-capita residential electricity consumption globally (50,669 kWh per capita; typical home: 14,000-16,000 kWh annually). Successful system deployment in Iceland demonstrates capability across all global markets. Design advancement target: 24/7/365 power delivery for fully electrified Icelandic household plus nightly charging of two 100+ kWh vehicles. Achievement of this target establishes global commercial viability.

## **6. Risk Assessment and Commercial Considerations**

### **Technical Risk**

Unvalidated wind acceleration subsystem represents primary technical risk. Mitigation: Prioritize Phase 1 independent testing; establish performance guarantees contingent on validation results; deploy conservative projections pending verification. All other system components employ proven commercial technology with established reliability profiles.

### **Market Risk**

Policy changes affecting net metering or renewable energy incentives could impact financial returns. Mitigation: Develop deployment strategy in jurisdictions with favorable and stable policies; create business models adaptable to varying regulatory environments; focus on regions with strong solar/wind resources and high electricity rates where financial case remains compelling under multiple policy scenarios.

### **Competitive Risk**

Existing solar and wind companies may develop similar integrated systems or utility companies may expand distributed generation offerings. Mitigation: Leverage patent protection; build early market share through first-mover advantage; develop proprietary software platform as defensible moat; establish licensing partnerships with regional installers.

### **Manufacturing and Supply Chain Risk**

System integration complexity and multi-component assembly introduce manufacturing risk. Mitigation: Establish relationships with established component manufacturers with proven supply chains; design for modular assembly; plan for distributed manufacturing in primary markets to reduce logistics costs and risks.

## Conclusion

The integrated distributed energy system described in Patent US 12,047,029 B2 is technically feasible and financially attractive. Based on conservative financial assumptions, the system delivers \$5,236 in annual benefits and achieves payback within 2.7 years, with 25-year net benefits exceeding \$146,900.

The market opportunity is substantial—over 1.33 billion addressable single-family homes globally represent a \$36 trillion market at system cost. Current penetration of distributed generation remains at 3-5%, indicating significant growth potential in coming decades.

Primary technical risk centers on validation of the active wind acceleration subsystem, which has not yet been independently tested. Successful completion of Phase 1 validation activities would enable Phase 2 commercial deployment with substantially reduced technical risk.

The system's integration of proven technologies with a novel wind acceleration approach, coupled with proprietary software for customer engagement and system optimization, creates a differentiated offering with defensible competitive advantages. Successful deployment would position the technology as a cornerstone solution for residential and commercial energy independence.

This technology merits serious investigation and investment from qualified partners capable of executing rigorous validation protocols, managing complex manufacturing and supply chain challenges, and deploying systems at scale across diverse geographic markets.